

## Technical Data Sheet

[www.soletex.com](http://www.soletex.com)

<b>Article- No</b>	KW 064 - PES - FAVORITE FLAG FABRIC	
<b>Application</b>	<b>Banner / Flags / Beach Flags</b>	
<b>Printable Ink</b>	Treatment applied for Sub Paper , Direct Sub., Latex, Uv-Curable	
<b>Material</b>	100 % Polyester	
<b>Standart Sizes</b>	App.103cm,155cm,310cm (40",61",122") x 100mt.(109 yrd.)	
<b>Weight</b>	110 ( g/m2 )+- 5(gr) (3,8 oz)	
<b>Tensile Strength</b>	27/95 warp/weft (daN)	DIN EN ISO 13934-1
<b>Tear Resistance</b>	8/13 warp/weft (N)	DIN EN ISO 13937-1
<b>Finishing</b>	Digital Coating	
<b>Packaging</b>	3" paper core, wrapped with stretch film + put in a cardboard box	

Our product enables to have vivid colors and good printing quality with SUB., LATEX & UV inks.

(Test printing is suggested before the printing job.)



Ink Type



Sub Direct and Paper Transfer



UV Printable



Latex Printable



Fire Retardant



Fire Retardant



Fire Retardant



European Standard



Cutting



Cold Cut

\*Optional



Be Green ♻️



All above released specifications and informations are for guidance purposes only. Our policy of continuous improvement may result in changes , we therefore reserve the right to alter the specifications and the informations at anytime without notice.